

# Brackets

## Pump House - Type 2 Brackets

These flat-packed, self assembly brackets provide a professional finish to the installation of wall mounted outdoor condensing units and air source heat pumps. The Type 2 brackets have a crossbar allowing the uprights to be spaced exactly as required, and include wall spacers to help level the unit on uneven walls. All components receive a powder coating, with a scratch resistant, textured finish in a colour (RAL 7032) to match most brands of condensing units and domestic air source heat pumps.

Integral Spirit Level

### Features:

- Integral spirit level makes correct installation of the crossbar easier.
- Uprights mount anywhere on the crossbar which enables the arm span to be adjusted easily.
- Adjustable wall spacers to level the arms.
- Safe working load up to 250 kg.
- Suitable to match most brands of condensing units and domestic air source heat pumps.
- Extra long arms (up to 1 metre available for larger condensing units).
- Textured finish in (RAL 7032).



Part Code	Description	Safe Working Load	Crossbar	Upright	Support Arm
CBR2-S	Type 2 Bracket - Small	60 kg	720 mm	400 mm	400 mm
CBR2-M	Type 2 Bracket - Medium	90 kg	900 mm	500 mm	500 mm
CBR2-L	Type 2 Bracket - Large	140 kg	1100 mm	550 mm	540 mm
CBR2-XL	Type 2 Bracket - Extra Large	250 kg	1040 mm	550 mm	660 mm

All brackets are tested to twice the safe working loads at an independent UK facility.